


SuperSpeed USB 3.0 Cables for El Ochito[®] Blue

SuperSpeed USB Cable

Glenair Part Number **963-118**

90 ohm commercial-grade cable features PVC jacket. SuperSpeed data pairs feature low dielectric constant foamed PE insulation. Each SuperSpeed pair has an aluminized polyester shield. Overall shield is aluminum foil and aluminum wire braid.

Construction Details



Color Code

SuperSpeed pairs VIO/ORN and BLU/YEL · Power wires RED, BLK · Low speed pair WHT/GRN.

Specifications


Impedance (ohms)		
High speed pairs	90 ± 7 (USB 3.0 pairs)	
Low-speed pair	90 ±15% (USB 2.0 pairs)	
Temperature Rating	0° to +80°C	
Voltage Rating	30V	
Intra-pair skew	15 ps/1.5m	
Differential to common mode	20 dB/cable @ 0.1 - 7.5 GHz	
Frequency (GHz)	IL (dB@1.5m)	NEXT (dB)
0.1	1.5	32
1.25	5.0	
2.5	7.5	32
3.0		23
7.5	25.0	23

SuperSpeed USB Cable

Glenair Part Number **963-110**

High performance, high temperature cable delivers dependable signal integrity over longer cable lengths. Fluoropolymer jacket can be laser-marked. Low-skew SuperSpeed data pairs have individual braid shields.

Construction Details



Color Code

SuperSpeed pairs VIO/ORN and BLU/YEL · Power wires RED, BLK · Low speed pair WHT/GRN.

Specifications

Impedance (ohms)	90 ± 5	
Temperature Rating	-65° to +200°C	
Voltage Rating	< 50 Vac	
Dielectric Withstanding Voltage	100 Vac rms	
Weight	57 g/m nominal	
Attenuation (SDD21)	Freq. (GHz)	dB/m max.
	.625	1.2
	1.25	1.7
	2.5	2.5
	5.0	3.9
	7.5	5.0