

600-076, 600-077, 600G004, 600G007 **Tools for Connector/Backshell Assembly Torque Wrenches**

ANALOG HAND-HELD TORQUE WRENCH



600G004 Hand-Held Torque Wrench with Analog Readout

Torque wrench features a 3/8" drive head and rotatable analog readout. Features a lighted and audible electric signal and is adjustable to desired torgue level from 0 to 150 inch pounds. Requires 9 volt battery (included).

ANALOG TORQUE WRENCH AND BENCH STAND



ANALOG HIGH TORQUE WRENCH AND BENCH STAND



600G007 Bench-Mount Torque Wrench with **Analog Readout**

Torque wrench features a 3/8" drive head and rotatable analog readout. Features a lighted and audible electric signal and is adjustable to desired torgue level from 0 to 150 inch pounds. Requires 9 volt battery (included).

600-077 Bench-Mount Torque Wrench with **Analog Readout**

Torgue wrench features a 3/8" drive head and analog readout. Lighted electric signal indicator and is adjustable to desired torque level from 20 to 360 inch pounds. Requires two Panasonic SR44W or equivalent batteries

© 2010 Glenair, Inc. MIL-DTL-38999 Cylindrical Connectors CAGE CODE 06324

GLENAIR, INC. • 1211 AIR WAY • GLENDALE, CA 91201-2497 • 818-247-6000 • FAX 818-500-9912 E-Mail: sales@glenair.com www.glenair.com H-54

ANALOG HAND-HELD, HIGH TORQUE WRENCH



600-076 Hand-Held High Torque Wrench with Analog Readout

Torque wrench features a dual sided 3/8" drive head for hand or bench mount use. Features a lighted electric signal and is adjustable to desired torque level from 20 to 360 inch pounds. Requires two Panasonic SR44W or equivalent batteries

Printed in U.S.A.