BATTLE-TESTED **STAR-PAN[™] NG**



Targeting Device Cables and Adapters TS8-547 TNR2i Side Hat, Ethernet And Composite Video Out, RPB

SPECIFICATIONS Unit pack: 1 ea. In ESD bag, heat-sealed. Include ESD dust cap. Tag and bag per illustration. Refer connector drawings 8070-1676 and 804-003 for connector materials, finishes and dimensions. Lengths to be measured straight. Jumper wires to be per M22759/11 To be used with TS1-037 **HOW TO ORDER Part Number:** TS8-547 **Cable Series** TNR2i Side Hat, Ethernet And Composite Video Out, RPB QUALIFIED FOR USE WITH ALL STAR-PAN POWER / DATA HUBS LIGHT, II, IV, AND VI HUB PORT DESIGNATOR: PAN LENGTH 'L' - SEE P/N DEVELOPMENT TOLERANCE: 'L' <= 60.00: +1.80/-0.00 'L' > 60.00: +3%/-0.00 12.00 + .75P2 TPE OVERMOLD USB TO ETHERNET CONVERTER IN OVERMOLD TYP. 1 Fc GLENAIR CONNECTOR, 804-003-01ZNU8-13S OR EQ. GLENAIR CONNECTOR, -8070-1676-06ZNU6-6PY INTERFACE IAW, 8070-1676-06ZNU6-6PY PIN 2 IS FMLB **P3** PIN 2 IS FMLB $6.00 \pm .50$ PIN 15 PIN 2 **PIN 24 PIN 16** PIN 8 PIN 23 **PIN 17 P1** PIN 27 -

© 2025 Glenair, Inc • 1211 Air Way, Glendale, CA 91201 • 818-247-6000 • www.glenair.com • U.S. CAGE Code 06324 • STAR-PAN" NG Dimensions in Inches (mm) are subject to change without notice.

PIN 12

| - PIN 5 - PIN 4 VIEW A-A PIN 13

PIN 20 — PIN 28

PIN 22