

The High-Speed Ultraminiature Connector for Harsh Environments

O-ring seals and epoxy potting for watertight sealing. Mates with 882-009, -018, -033, -036.



Selection Guide: El Ochito® Blue for USB 3.0

Quick Disconnect for USB 3.0			
W.	882-009 Cable Plug		882-033 90° PCB Plug54 Rear panel mount, jam-nut plug with O-ring seals and epoxy potting for watertight sealing. Mates with 882-010, -013, -016, 039.
O TON	882-010 Cable Receptacle		882-016 90° PCB Receptacle
	882-036 Panel Mount Plug	- Min	8572-0006 Cordset, Single-ended56 Pre-wired with aerospace-grade or commercial-grade USB 3.0 cable. Cable has Superfly connector on one end, other end is unterminated.
	882-039 Panel Mount Receptacle51 Integral backshell and cable grommet. Supplied as unassembled kit for termination to USB 3.0 cable. Mates to 882-009, -018, -033, -036.	The state of the s	8572-0007 Cordset, Double-ended 57 Pre-wired with aerospace-grade or commercial-grade USB 3.0 cable. Cable has Superfly plug on one end and receptacle on the other end.
	882-018 PCB Plug		8572-0008 Patchcord, USB58 Pre-wired patchcord with commercial-grade USB 3.0 cable. Cable has Superfly connector on one end, opposite end is standard USB connector.
~	882-013 PCB Receptacle53 Rear panel mount, jam-nut receptacle with		



Selection Guide: El Ochito® Blue for USB 3.0

Threaded Coupling for USB 3.0



882-011 Cable Plug59

Integral backshell and cable grommet. Supplied as unassembled kit for termination to USB 3.0 cable. Mates with 882-012, -014, -015, and -042.



882-015 90° PCB Receptacle......63

Rear panel mount, jam-nut receptacle with O-ring seals and epoxy potting for watertight sealing. Mates with 882-011.



882-014 Cable Receptacle......60

Integral backshell and cable grommet. Supplied as unassembled kit for termination to USB 3.0 cable. Mates with 882-011.



8572-0010 Cordset, Single-ended......64

Pre-wired with aerospace-grade or commercialgrade USB 3.0 cable. Cordset has SuperFly connector on one end, opposite end is unterminated.



882-042 Panel Mount Receptacle61

Integral backshell and cable grommet.
Supplied as unassembled kit for termination to USB 3.0 cable. Mates with 882-011.



8572-0011 Cordset, Double-ended.......65

Pre-wired with aerospace-grade or commercialgrade USB 3.0 cable. Cordset has SuperFly plug on one end and receptacle on opposite end.



882-012 PCB Receptacle62

Rear panel mount, jam-nut receptacle with O-ring seals and epoxy potting for watertight sealing. Mates with 882-011.



8572-0013 Patchcord66

Pre-wired with commercial-grade USB 3.0 cable. Cable has standard USB connector on one end, other end is SuperFly connector

90 ohm USB 3.0 Cables



963-110 Flight-Grade Cable67

High temperature, high performance, fluoropolymer materials, shielded. High speed pairs have braid shields. -65° to +200°C.



963-118 Commercial-Grade Cable67

Black PVC jacket, foamed PE wire insulation. High speed pairs have foil shields. 0 to +80°C.