SuperNine® High-Speed Series



MIL-DTL-38999 Series III Type Environmental Connectors 8572-0001 Pre-wired El Ochito[®] USB 3.0 contacts, single-ended



Ochito "Blue" for SuperSpeed USB Pin contact mating face

Contact Positions


3
3
4
7
6
5
Mating face of Socket

■ Refer to individual contact and cable data sheets for construction details

- 100% tested for shorts, continuity and IR
- Operating temperature
 Aero: -65° to +125°C
 Commercial: 0 to 80°C
- Impedance: 90 ohms
- **DWV:** 500 Vrms
- Current Rating: 1.5 A
- IR: 200 megohms min.
- Durability: 500 mating cycles

OCHITO CONTACT 1 2 YEL 3 RED 4 BLK 5 ORN 6 VIO 7 GRN 8

Two cable options: commercial grade or flight-grade. 100% tested. Save assembly time and cost with pre-wired El Ochito® "Blue" SuperSpeed USB assemblies. These single-ended assemblies have Ochito "Blue" contacts terminated to USB 3 shielded cables. Supplied with cable sealing boot. Commercial-grade version has PVC jacket. Aerospace-grade version has high temperature fluoropolymer construction and braided shields on SuperSpeed pairs. Compatible with Glenair Series 23 connectors. Ochito contacts should be installed in keyed connectors before mating to prevent misalignment and contact damage.



Part Number Development								
Sample Part Number	8572-0001	-01	-36					
Series / Basic Part No.	8572-0001 = Pre-wired El Ochito® contact, with USB 3.0 cable							
Order Code	See Table I							
Length	Length in inches (12 inch minimum)							

Table I: Order Code									
Connector Type	Order Code	Pin Contact Part No.	Order Code	Skt. Contact Part No.	Cable Type	Cable Part Number			
Series 23	01	858-028-01F	03	858-029-01F	Commercial-grade PVC Jacket 0° to +80°C	963-118			
	02	858-028-02F	04	858-029-02F	Aerospace-grade Fluoropolymer Jacket -65° to +125°C	963-110			