

GS22759-45

Nickel-Coated Copper Wire with Lightweight Modified XL-ETFE Insulation

NOTES

1. Wire is made in accordance with AS22759/45.
2. Conductor is nickel-coated copper per AS29606.
3. Insulation is crosslinked modified ETFE
4. Wire maximum continuous temperature rating is 200°C (392°F).
5. Voltage rating is 600 volts (RMS) at sea level.
6. Color code per MIL-STD-681. See MIL-STD-681 for additional wire color codes. Jacket color code must be white (9) if adding color stripes.
7. Consult factory for custom stripe color order.

HOW TO ORDER

Sample Part Number	GS22759-45	-24	-9	0	1	2
Basic Part Number	GS22759-45					
Wire Size	See Table I					
Jacket Color Code	See Table II					
First Stripe Color Code	(Omit for none) See Table II					
Second Stripe Color Code	(Omit for none) See Table II					
Third Stripe Color Code	(Omit for none) See Table II					

Small Diameter Nickel-Coated
Stranded Copper Conductor

Insulation-crosslinked modified ETFE




Table II: Jacket and Stripe Color Codes

Color code	Color
0	Black
1	Brown
2	Red
3	Orange
4	Yellow
5	Green
6	Blue
7	Violet
8	Gray
9	White

Table I: Part Number and Wire Specifications

Part Number	Wire Size	Stranding (Number of strands x size gage of strands)	Diameter of stranded conductor (inches)		Finished Wire		
			min	max	Resistance at 20° C (68° F) (Ohms/ 1000 ft) max	Diameter (inches)	Weight (lbs/1000 ft) max
GS22759-45-28-*	28	7 X 36	.0135	.0164	67.9	.027±.002	.91
GS22759-45-26-*	26	19 X 38	.0175	.0204	42.2	.032±.002	1.4
GS22759-45-24-*	24	19 X 36	.0225	.0254	25.9	.037±.002	2.0
GS22759-45-22-*	22	19 X 34	.0285	.0314	16.0	.043±.002	2.8
GS22759-45-20-*	20	19 X 32	.0365	.0394	9.77	.050±.002	4.3
GS22759-45-18-*	18	19 X 30	.0455	.0494	6.10	.060±.002	6.5
GS22759-45-16-*	16	19 X 29	.0515	.0554	4.76	.068±.002	8.3
GS22759-45-14-*	14	19 X 27	.0645	.0694	3.00	.085±.003	13.0
GS22759-45-12-*	12	37 X 28	.0835	.0894	1.98	.103±.003	19.7